


# Michielse-Techniek

## High Pressure components

### Engineering & Construction

#### Bi-directional HIGH PRESSURE VALVES

- 20,000/30,000/43,000/66,000 PSI
- MAWP up to 66,000psi (4500 bar).
- Available in sizes 1/4", 3/8", 1/2" 9/16" and 1".
- Single panel mount locking device.
- Nonrotating upper-to-lower stem connection.
- Temperatures up to 600°F(316°C)
- Manufactured from cold worked 316 stainless steel (Other material available)
- Bi-directional 2-way straight and angled
- 3-way and 2-stem manifold valves available.
- Full open in 4-5 turns (1/4",3/8",1/2" 9/16")
- End connection styles: Medium and High Pressure Cone and Thread, NPT Thread



#### **Assembly Valve**

**15,000 PSI, 3/8" NPT, 2-Way Straight, 2 Piece V-Stem  
Standard Handle**

*\*Dimensions are subject to change and are considered reference.*

#### Leveringspakket :

- Afsluiters
- Dynamische afdichtingen
- Statische afdichtingen
- Mechanical seals
- RVS filterelementen
- Rubber Vormwerk
- Constructie, plaat- en leidingwerk
- Machinale verspaning
- Service

#### Contact :

Michielse-Techniek  
engineering & constructie  
Info@michielse-techniek.nl  
0031(0)8 587 695 29  
www.Michielse-Techniek.nl